

Straight Blade Devices 30A, 125/250V, 3 Pole, 3 Wire Non-Grounding Plug

HUBBELL



Features

- Supertough nylon housing
- Gripping ribs provide secure gripping area
- Captive Allen head terminal screws are user-ready

Ordering Information

Description	Cord Diameter	UPC	Catalog Number
Plug, Insulgrip®, nylon	.625"-1.00" (15.9-25.4)	783585015699	HBL9337C



Listings


UL Listed File E1706
CSA Certified

Specifications

Housing	Supertough Nylon
Blade Holder	Reinforced Thermoplastic Polyester
Blades	Brass
Box Terminals	Copper Alloy
Cord Clamps	Reinforced Thermoplastic Polyester

Performance

Electrical	
Current Interrupting	Certified for current interrupting at full rated current
Dielectric Voltage	Withstands 2,000V minimum
Mechanical	
Product Identification	Ratings are a permanent part of the device
Terminal Accommodation	#12 AWG through #4 AWG copper wire only
Terminal Identification	Terminals identified in accordance with UL 498 and CSA
Environmental	
Flammability	UL 94 HB
IP Suitability	IP20
Operating Temperatures	Maximum continuous 75°C; minimum -40°C (w/o impact)



Resources

Customer Use Drawing
eCatalog

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

